

Product Data Sheet

Revised: 2021/02/08 (version 1.0)

PETRONAS Syntium 800



5W-30

Designed with °CoolTech™ technology to fight excessive engine heat

Modern driving conditions such as stop-start driving, idling in traffic jams, acceleration on highways, driving up steep hills and many more put engines under a lot of stress that can lead to excessive heat buildup. Excessive engine heat generation is not limited to a particular country or driving pattern; it is a common issue engines face across the globe.

Description and Applications

PETRONAS Syntium 800 5W-30 is a semi synthetic lubricant that is formulated with °CoolTech™ to fight excessive engine heat. °CoolTech™ targets the critical heat zones – parts that are affected by excessive heat inside the engine – to effectively absorb and transfer excessive heat to regulate temperature within the engine; defending the engine's critical components from damage and loss of performance.

PETRONAS Syntium 800 5W-30 is designed to meet the latest API SP and ILSAC GF-6 specifications and is suitable for some types of passenger cars running on gasoline (please refer to the owner's manual).

Benefits

PETRONAS Syntium 800 5W-30 is formulated with °CoolTech™ to fight excessive engine heat for optimum engine performance and to defend the engine's critical components through:

- Superior protection against premature wear of engine parts.
- Superior sludge prevention capability for gasoline applications to protect engines from seizing up.

Approvals, Specifications and Recommendations

Specifications:

- API SP
- ILSAC GF-6A

Note: Always consult your owner's manual to check for recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density @15°C	ASTM D 4052	g/cm ³	0.853
Kinematic Viscosity @100°C	ASTM D 445	mm ² /s (cSt)	9.9
Viscosity Index	ASTM D 2270	-	155
Flash Point COC	ASTM D 92	°C	232
Sulphated Ash	ASTM D 874	%	0.61
TBN	ASTM D 2896	mgKOH/g	7.2
CCS at -30°C	ASTM D5293	mPa·s	5609
Pour Point	ASTM D97	°C	-39

All technical data are provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refers to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 70677