

PETRONAS HTO SERIES

High Performance Heat Transfer Fluids

PETRONAS HTO Series are high performance heat transfer fluids specially developed for open and enclosed heat transfer systems operating at high bulk oil temperatures. Formulated with high quality selected mineral base oils enhanced with advanced anti-oxidant and detergent additives, PETRONAS HTO fluids provide high anti-oxidant protection and detergency to eliminate build-up and deposits.

Applications

PETRONAS HTO Series fluids are recommended for use in:

- open and enclosed circulated heat transfer systems
- petroleum product processing
- rubber, textile and plastics industries
- Solar energy heat transfer and storage

Features and Benefits

Features	Benefits
Excellent heat transfer rates	Maintains excellent thermal conductivity which improves system efficiency
High thermal and oxidation stability	Provides high oxidation stability at elevated temperatures and avoid thermal cracking up 310°C Minimizes sludge and acid formation
High compatibility with most seal and elastomers	Compatible with most seals and elastomers, which prevents oil leaks and contamination due to seal erosion

PETRONAS HTO SERIES

High Performance Heat Transfer Fluids

Typical Properties

Characteristic	Method	Specification	22	32	46
Specific Gravity @15°C	ASTM D 4052	(1)	0,868	0,871	0,877
Kinematic Viscosity at 40°C, cSt	ASTM D 445	(1)	22	32	46
Kinematic Viscosity at 100°C, cSt	ASTM D 445	(1)	4,3	5,4	6,8
Viscosity Index	ASTM D 2270	(1)	101	102	102
Flash Point, °C	ASTM D 92	(1)	170	220	230
Pour Point, °C	ASTM D 97	(1)	-18	-15	-12
TAN, mgKOH/g	ASTM D 664	(1)	0,10	0,10	0,10
Copper Strip Corrosion	ASTM D 130	(1)	1b	1b	1b
Oil load temperature ranges: closed system			-7°C to 255°C	-4°C to 305°C	-2°C to 315°C
Oil load temperature ranges: open system			-7°C to 130°C	-4°C to 180°C	-2°C to 190°C

All technical data is provided for reference only / SS is available upon request including quality control limits / (1): not required in specification

Performance Levels

- DIN 51522
- ISO 6743-12 Family Q

PETRONAS HTO SERIES

High Performance Heat Transfer Fluids

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refers to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contains herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.